

13 JUN 2005

539, 915

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number  
**WO 2004/055327 A1**

- (51) International Patent Classification<sup>7</sup>: **E21D 21/00**
- (21) International Application Number:  
PCT/AU2003/001667
- (22) International Filing Date:  
16 December 2003 (16.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2002953368 16 December 2002 (16.12.2002) AU
- (71) Applicant (for all designated States except US): **GARFORD PTY LTD** [AU/AU]; 66 Paramount Drive, Wangara, Western Australia 6065 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **HEDRICK, Neville** [AU/AU]; 66 Paramount Drive, Wangara, Western Australia 6065 (AU).
- (74) Agent: **LORD & COMPANY**; 4 Douro Place, West Perth, Western Australia 6005 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A YIELDING ROCK BOLT



(57) Abstract: A yielding rock bolt (10) having a solid metal shaft (12) with a relatively wide portion (64) and a relative narrow portion (60) and an anchor member (14) mounted about the shaft (12). The anchor member (14) has longitudinal bore (40) which is of lesser dimension than the relatively wide portion (64). The anchor member (14) is mounted about the relatively narrow portion (60) adjacent the wide portion (64). In use the shaft (12) is extruded through the anchor member (14) to cause the rock (10) to yield as a rock face moves.

WO 2004/055327 A1